

Magical Red Pink E10

Quinacridone

C.I. Pigment Red 122
Colour Index No. 73915



Technical Application Data

	HDPE	PVC
Heat Stability(C°)	300	—
Light Fastness SD $\frac{1}{3}$ Full Shade	8	8
Light Fastness SD $\frac{1}{3}$ Reduction	8	8
Weather Fastness SD $\frac{1}{3}$ Full Shade	5	5
Weather Fastness SD $\frac{1}{3}$ Reduction	5	4-5
Fastness to bleed	—	5

Physical Characteristics

CAS No:	980-26-7
Density(g/cm ³)	1.45
Alkali resistance	5
Acid resistance	5
Specific surface(m ² /g)	64

Range of Applications

						Spin Dyeing	
LDPE	●	PP	●	PC	●	PP	●
HDPE	●	Rubber	●	PBT	●	PET	●
PUR	●	PS/SAN	●	PA	—	PA	●
PVC	●	ABS	●	POM	●	PAN	—

Commentary

A pigment with excellent fastness properties and outstanding dispersibility. Suitable for high-tech applications and for most plastics. Highly recommended for fibre, film and thin-wall applications. Excellent fastness to weathering.

Note : Data Presented above is based on our present knowledge and is with intentions of providing general guidelines for use of our products. These products are offered by TINTEC without any kind of guarantee. We recommend that customers should test the suitability of these products in their end application before use.