# **Magicol Yellow HGR**

Monoazo / Ca lake



C.I. Pigment Yellow 191 Colour Index No. 18795

#### **Technical Application Data**

	HDPE	PVC
Heat Stability(C°)	300	_
Light Fastness SD $^{1}\!\!/_{3}$ Full Shade	7	7
Light Fastness SD $\frac{1}{3}$ Reduction	6-7	6
Weather Fastness SD <sup>1</sup> / <sub>3</sub> Full Shade	3	—
Weather Fastness SD <sup>1</sup> / <sub>3</sub> Reduction	-	_
Fastness to bleed	5	5

## **Physical Characteristics**

CAS No:	129423-54-7
Density( g/cm <sup>3</sup> )	1.75
Alkali resistance	5
Acid resistance	5
Specific surface( m <sup>2</sup> /g)	22

## **Range of Applications**

						Spin Dyeing	
LDPE	•	РР	•	PC	0	PP	•
HDPE	•	Rubber	•	PBT	0	PET	_
PUR	•	PS/SAN	0	PA	_	PA	-
PVC	•	ABS	0	POM	_	PAN	_

### Commentary

A economical red shade yellow pigment with excellent heat stability and resistance properties. Ideal replacement for diarylide and lead chromate pigments.

Note : Data Presented above is based on our present knowledge and is with intentions of providing general guidelines for use of our products. These products are offered by TINTEC without any kind of guarantee. We recommend that customers should test the suitability of these products in their end application before use.