

Magical Red D3G 02

DPP

C.I. Pigment Red 254
Colour Index No. 56110



Technical Application Data

	HDPE	PVC
Heat Stability(C°)	300	—
Light Fastness SD $\frac{1}{3}$ Full Shade	8	8
Light Fastness SD $\frac{1}{3}$ Reduction	8	8
Weather Fastness SD $\frac{1}{3}$ Full Shade	5	5
Weather Fastness SD $\frac{1}{3}$ Reduction	5	4-5
Fastness to bleed	—	5

Physical Characteristics

CAS No:	84632-65-5
Density(g/cm ³)	1.58
Alkali resistance	5
Acid resistance	5
Specific surface(m ² /g)	28

Range of Applications

						Spin Dyeing	
LDPE	●	PP	—	PC	—	PP	●
HDPE	●	Rubber	●	PBT	—	PET	—
PUR	●	PS/SAN	●	PA	—	PA	—
PVC	●	ABS	●	POM	—	PAN	—

Commentary

A brilliant high performance pigment, with middle shade, excellent color strength and dispersibility, and outstanding fastness properties, mainly recommended for EVA, PVC and PO.

Note : Data Presented above is based on our present knowledge and is with intentions of providing general guidelines for use of our products. These products are offered by TINTEC without any kind of guarantee. We recommend that customers should test the suitability of these products in their end application before use.