## LUCIDUS GREEN 5B



C.I. Solvent Green 3
Colour Index No. 61565

<b>Technical Application Data</b>	
-----------------------------------	--

Anthraquinone

	PS	ABS	PC	PET	PA 6
Heat Stability(C°)	300	300	340	300	_
Light Fastness SD $^{1}\!\!/_{3}$ Full Shade	7	5	7	7	—
Light Fastness SD $\frac{1}{3}$ Reduction	6	4	6	6	_

## **Physical and Chemical Characteristics**

Shade	Bluish green
CAS No.	128-80-3
Density(g/cm <sup>3</sup> )	1.31
Melting point(C°)	215
Alkali resistance	5
Acid resistance	5

## **Range of Applications**

						Spin Dyeing	
PS	•	РС	•	PMMA	•	PET	-
SAN	•	PET	•	PA 6	_	РА	_
ABS	•	PBT	•	PA 66	_	PAN	—

## Commentary

Lucidus Green 5B is bluish green with very good light fastness and excellent heat resistance, structurally halogen free, suitable for E & E applications.

Note : Data Presented above is based on our present knowledge and is with intentions of providing general guidelines for use of our products. These products are offered by TINTEC without any kind of guarantee. We recommend that customers should test the suitability of these products in their end application before use.